

**Description**

Thread Size: 3/16", Nut Length: 53/64", Nut Height: 25/64", fine thread, two holes, NAS1474 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1474F3
Minimum Qty (MOQ):	5
NSN:	5310-01-310-5252
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS1474F3 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.220 Inches Minimum Nut
<b>Mounting Hole Diameter:</b>	0.098 Inches Nominal
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.840 Inches Maximum
<b>Nut Height:</b>	0.405 Inches Maximum
<b>Plate Thickness:</b>	0.030 Inches Maximum
<b>Plate Width:</b>	0.443 Inches Maximum
<b>Nut Counterbore Depth:</b>	0.070 Inches Minimum Nut
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.290 Inches Minimum And 0.300 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.589 Inches Minimum And 0.592 Inches Maximum
<b>Temp Rating:</b>	350.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Special Features:</b>	Seal Color Blue
<b>Material:</b>	Iron Alloy 660 Nut
<b>Material:</b>	Iron Alloy 660 Shell
<b>Material:</b>	Iron Alloy 660 Washer
<b>Material:</b>	Rubber Fluorosilicone Class Fq Seal
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Shell
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Washer Or Ams 5732 Assn Std Single Material Response Washer
<b>Material Document And Classification:</b>	Mil-r-25988,ty 2,cl 1 Mil Spec Single Material Response Seal

<b>Surface Treatment:</b>	Cadmium Washer And Chromate Washer
<b>Surface Treatment:</b>	Cadmium Nut And Chromate Nut
<b>Surface Treatment:</b>	Cadmium Shell And Chromate Shell
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Nut
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Washer
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Shell
<b>Specification/standard Data:</b>	80205-nas1474 Professional/industrial Association Standard

## How to Order

Order this self-locking nutplate from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/NAS1474F3](https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474F3) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.