

## **P/N NAS1474F4**

### **Description**

Thread Size: 1/4", Nut Length: 1", Nut Height: 11/32",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1474F4

Minimum Qty (MOQ): 5

NSN: 5310-01-264-5904

Schedule B: 7318.16.0030

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1474F4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	
	0.280 Inches Nominal First End
Lubrication:	Dry Film Lubricant
Overall Height:	0.560 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Nominal
Nut Style:	Plate
Nut Length:	1.000 Inches Maximum
Nut Height:	0.350 Inches Maximum
Plate Thickness:	0.030 Inches Maximum
Plate Width:	0.635 Inches Maximum
Nut Counterbore Depth:	0.105 Inches Nominal First End
Nut Mounting Provision:	Straight Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Temp Rating:	65.0 Deg Fahrenheit Minimum And 350.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Rubber Fluorosilicone Class Fq Seal
Material:	Steel Corrosion Resisting Nut
Material Document And Classification:	Mil-r-25988 Mil Spec Single Material Response Seal
Surface Treatment:	Passivate Nut
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Nut
Specification/standard Data:	80205-nas1474 Professional/industrial Association Standard

## **How to Order**

