

Description

Thread: 10-32, Thread Size: 3/16", Nut Length: 53/64", Nut Height: 17/64, 5310-01-244-2258

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[NAS1474-R3](#)

SKU / Model:	NAS1474R3
Minimum Qty (MOQ):	5
NSN:	5310-01-244-2258
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1474R3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.220 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Overall Height:	0.405 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Nominal
Nut Style:	Plate
Nut Length:	0.840 Inches Maximum
Nut Height:	0.268 Inches Maximum
Plate Thickness:	0.030 Inches Maximum
Plate Width:	0.443 Inches Maximum
Nut Counterbore Depth:	0.070 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.290 Inches Minimum And 0.300 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.588 Inches Minimum And 0.592 Inches Maximum
Temp Rating:	65.0 Deg Fahrenheit Minimum And 225.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	60.0 Shore Durometer A Nominal
Nominal Thread Size:	0.190 Inches
Material:	Iron Alloy 660 Nut
Material:	Iron Alloy 660 Shell
Material:	Iron Alloy 660 Washer
Material:	Rubber Butadiene-acrylonitrile Class Nbr Seal
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Shell

Material Document And Classification:	Ams 5525 Assn Std Single Material Response Washer Or Ams 5732 Assn Std Single Material Response Washer
Material Document And Classification:	Mil-r-6855,class 1,grade 60 Mil Spec Single Material Response Seal
Surface Treatment:	Passivate Nut
Surface Treatment:	Passivate Shell
Surface Treatment:	Passivate Washer
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Nut
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Shell
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Washer
Specification/standard Data:	80205-nas1774 Professional/industrial Association Standard

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1474R3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.