

## **P/N NAS1474R4**

## **Description**

Thread Size: 1/4", Nut Length: 1", Nut Height: 11/32", two lug

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS1474R4

Minimum Qty (MOQ): 2

NSN: 5310-01-248-1964

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1474R4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature: Counterbore Diameter:	Prevailing Torque All Metal Design  0.280 Inches Minimum Nut
Overall Height:	0.560 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Nominal
Nut Style:	Plate
Nut Length:	1.000 Inches Maximum
Nut Height:	0.350 Inches Maximum
Plate Thickness:	0.030 Inches Maximum
Plate Width:	0.635 Inches Maximum
Nut Counterbore Depth:	0.105 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.371 Inches Minimum And 0.381 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.750 Inches Minimum And 0.754 Inches Maximum
Temp Rating:	-65.0 Deg Fahrenheit Minimum And 225.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Hardness Rating:	60.0 Shore Durometer A Nominal
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Nut
Material:	Iron Alloy 660 Shell
Material:	Iron Alloy 660 Washer
Material:	Rubber Butadiene-acrylonitrile Class Nbr Seal
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Shell
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Washer Or Ams 5732 Assn Std Single Material Response Washer

Material Document And Classification:	Mil-r-6855,cl 1,grade 60 Mil Spec Single Material Response Seal
Surface Treatment:	Passivate Nut
Surface Treatment:	Passivate Shell
Surface Treatment:	Passivate Washer
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Nut
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Shell
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Washer
Specification/standard Data:	80205-nas1474 Professional/industrial Association Standard

## **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1474R4">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1474R4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1474R4">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1474R4</a> and selecting the