

Description

Fastener Length: 3-45/64", Thread: 3/8-20, Head Width: 3/8", Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS147A59 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-228-3909 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS147A59 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.798 Inches Minimum And 0.828 Inches Maximum |
| Fastener Length: | 3.673 Inches Minimum And 3.703 Inches Maximum |
| Head Diameter: | 0.740 Inches Minimum And 0.750 Inches Maximum |
| Head Height: | 0.407 Inches Nominal |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Minimum First Hole And 0.111 Inches Maximum First Hole |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.437 Inches |
| Width Across Flats: | 0.375 Inches Minimum And 0.378 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 3.391 Inches Nominal First Hole |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 3140 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas147 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS147A59> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.