



Military-Fasteners.com

P/N NAS147A59

Description

Fastener Length: 3-45/64", Thread: 3/8-20, Head Width: 3/8", Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS147A59
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-228-3909
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS147A59 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.798 Inches Minimum And 0.828 Inches Maximum
Fastener Length:	3.673 Inches Minimum And 3.703 Inches Maximum
Head Diameter:	0.740 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.407 Inches Nominal
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.111 Inches Maximum First Hole
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.437 Inches
Width Across Flats:	0.375 Inches Minimum And 0.378 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	3.391 Inches Nominal First Hole
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 3140 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas147 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS147A59> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.