



Description

Fastener Length: 1-3/4", Thread: 1/2-20, Head Width: 1/2", Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS14828
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-835-5714
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS148-28 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.788 Inches Minimum And 0.838 Inches Maximum
Fastener Length:	1.735 Inches Minimum And 1.765 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	0.802 Inches Minimum And 0.813 Inches Maximum
Head Height:	0.460 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.500 Inches Minimum And 0.503 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 3140 Overall Or Steel Comp 3135 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas148 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS148-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.