

Description

Fastener Length: 1-3/4", Thread: 1/2-20, Head Width: 1/2", Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS14828 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-835-5714 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS148-28 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.788 Inches Minimum And 0.838 Inches Maximum |
| Fastener Length: | 1.735 Inches Minimum And 1.765 Inches Maximum |
| Head Style: | Bevel-conical |
| Head Diameter: | 0.802 Inches Minimum And 0.813 Inches Maximum |
| Head Height: | 0.460 Inches Nominal |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.500 Inches |
| Width Across Flats: | 0.500 Inches Minimum And 0.503 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 3140 Overall Or Steel Comp 3135 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas148 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS148-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.