

P/N NAS1503-2

Description

Fastener Length: 13/32", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS15032

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-833-5306

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1503-2 Specifications

Thread Direction: Right-hand Thread Direction: Right-hand O. 276 Inches Minimum And 0.416 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.328 Inches Minimum And 0.385 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.385 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.190 Inches Grip Length: 0.125 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mils-5626 Mil Spec 1st Material Response Overall Or Mils-5000 Mil Spec 2nd Material Response Overall Or Mils-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unf Specification/standard Data: 80205-nas1503 Professional/industrial Association Standard	Thread Class:	3a
Thread Length: 0.276 Inches Minimum Fastener Length: 0.386 Inches Minimum And 0.416 Inches Maximum Head Style: Flat Countersunk Head Dlameter: 0.328 Inches Minimum And 0.385 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.190 Inches Grip Length: 0.125 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Alies-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overa		
Fastener Length: 0.386 Inches Minimum And 0.416 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.328 Inches Minimum And 0.385 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.190 Inches Grip Length: 0.125 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 10.10 Degrees Maximum Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment Document And Classification: 0q-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf		
Head Style: Flat Countersunk Head Diameter: 0.328 Inches Minimum And 0.385 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.190 Inches Grip Length: 0.125 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 160000 Pounds Per Square Inch Hardness Rating: 160000 Pounds Per Square Inch Hardness Rating: 160000 Pounds Per Square Inch Material: 160000 Pounds Per Square Inch Mill-s-5626 Mill Spec Stinimum And 101.0 Degrees Maximum Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mill-s-5626 Mill Spec 1st Material Response Overall Or Mill-s-5000 Mill Spec 2nd Material Response Overall Or Mill-s-6049 Mill Spec Sth Material Response Overall Or Mill-s-6098 Mill Spec 4th Material Response Overall Or Mill-s-6049 Mill Spec 5th Material Response Overall Surface Treatment Document And Classification: 17000 Qr.p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Thread Length:	0.276 Inches Minimum
Head Diameter: 0.328 Inches Minimum And 0.385 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.190 Inches Grip Length: 0.125 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mi	Fastener Length:	0.386 Inches Minimum And 0.416 Inches Maximum
Grip Diameter: Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.190 Inches Grip Length: 0.125 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hardness Rating: 0.600 Pounds Per Square Inch Hardness Rating: 0.90. Degrees Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Document And Classification: Agriface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unf	Head Style:	Flat Countersunk
Internal Drive Style: Offset Cruciform (torque Set) Nominal Thread Diameter: 0.190 Inches Grip Length: 0.125 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mils-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Re	Head Diameter:	0.328 Inches Minimum And 0.385 Inches Maximum
Nominal Thread Diameter: Grip Length: 0.125 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Document And Classification: Wiffice Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unf	Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Grip Length: O.125 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Document And Classification: Ard Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unf	Internal Drive Style:	Offset Cruciform (torque Set)
Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall	Nominal Thread Diameter:	0.190 Inches
Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Ove	Grip Length:	0.125 Inches Nominal
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or	Thread Quantity Per Inch:	32
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8745 Overall Or Steel Comp 8745 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Mil-s-6060 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil S	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unf	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material Document And Classification:3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Material:	
Surface Treatment Document And Classification: Thread Series Designator: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Unf	Material Document And Classification:	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material
Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Surface Treatment:	Cadmium Overall And Chromate Overall
		Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas1503 Professional/industrial Association Standard	Thread Series Designator:	Unf
	Specification/standard Data:	80205-nas1503 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1503-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1503-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1503-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1503-2 and selecting the quantity you want then click "add to cart".