

Description

size: 3/8", packing with retainer, alloy steel with nitrile synthetic rubber

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS15236Y
Minimum Qty (MOQ):	20
NSN:	5330-00-003-9302
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N NAS1523-6Y Specifications

Outside Diameter:	0.651 Inches Minimum And 0.676 Inches Maximum
Retainer Thickness:	0.045 Inches Minimum And 0.055 Inches Maximum
Packing Ring Cross-sectional Diameter:	0.067 Inches Minimum And 0.077 Inches Maximum
Packing Inside Diameter:	0.354 Inches Minimum And 0.374 Inches Maximum
Construction:	One-piece
Material:	Rubber Butadiene-acrylonitrile Class Nbr Packing
Material:	Steel Comp 4130 Retainer
Material Document And Classification:	Mil-r-7362,ty 2 Mil Spec Single Material Response Packing
Material Document And Classification:	Mil-s-18729 Mil Spec Single Material Response Retainer
Surface Treatment:	Cadmium Retainer And Chromate Retainer
Surface Treatment Document And Classification:	Qq-p-416,cl 3 Fed Spec All Treatment Responses Retainer
Specification/standard Data:	80205-nas 1523 Professional/Industrial Association Standard

How to Order

Order this packing with retainer from our inventory online by visiting https://military-fasteners.com/o_rings/packing+with+retainers/NAS1523-6Y and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.