

**Description**


size: #10, packing with retainer, alloy steel with fluorinated silicone

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1523AA3R
Minimum Qty (MOQ):	10
NSN:	5330-01-097-8065
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



## P/N NAS1523AA3R Specifications

<b>Outside Diameter:</b>	0.433 Inches Minimum And 0.458 Inches Maximum
<b>Retainer Thickness:</b>	0.045 Inches Minimum And 0.055 Inches Maximum
<b>Packing Ring Cross-sectional Diameter:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Packing Inside Diameter:</b>	0.170 Inches Minimum And 0.190 Inches Maximum
<b>Construction:</b>	One-piece
<b>Material:</b>	Aluminum Alloy 7075 Retainer
<b>Material:</b>	Rubber Fluorosilicone Class Fq Packing
<b>Material Document And Classification:</b>	Mil-r-25988 Ty 2 Cl 1 Gr 60 Mil Spec Single Material Response Packing
<b>Material Document And Classification:</b>	Qq-a-250/12 T6 Fed Spec Single Material Response Retainer
<b>Surface Treatment:</b>	Anodize Retainer
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Ty 2 Cl 1 Mil Spec Single Treatment Response Retainer
<b>Specification/standard Data:</b>	80205-nas 1523 Professional/Industrial Association Standard

## How to Order

Order this packing with retainer from our inventory online by visiting [https://military-fasteners.com/o\\_rings/packing+with+retainers/NAS1523AA3R](https://military-fasteners.com/o_rings/packing+with+retainers/NAS1523AA3R) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.