

Description

size: #10, packing with retainer, corrosion resistant steel with fluorinated silicone

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1523C3R
Minimum Qty (MOQ):	20
NSN:	5330-01-101-9492
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE
AVAILABLE

P/N NAS1523C3R Specifications

Outside Diameter:	0.433 Inches Minimum And 0.458 Inches Maximum
Retainer Thickness:	0.045 Inches Minimum And 0.055 Inches Maximum
Packing Ring Cross-sectional Diameter:	0.067 Inches Minimum And 0.077 Inches Maximum
Packing Inside Diameter:	0.170 Inches Minimum And 0.190 Inches Maximum
Construction:	One-piece
Material:	Rubber Synthetic Packing
Material:	Steel Comp 301 Retainer Or Steel Comp 302 Retainer
Material Document And Classification:	Mil-s-5059 Cond Half Hard Or Annealed Mil Spec All Material Responses Retainer
Surface Treatment:	Passivate Retainer
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Retainer
Specification/standard Data:	80205-nas 1523 Professional/industrial Association Standard

How to Order

Order this packing with retainer from our inventory online by visiting https://military-fasteners.com/o_rings/packing+with+retainers/NAS1523C3R and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.