

**Description**

size: 1/4", corrosion resistant steel with fluorinated silicone, NAS1523 series oring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1523C4R
Minimum Qty (MOQ):	10
NSN:	5330-01-049-8254
Schedule B:	4016.93.5010
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N NAS1523C4R Specifications

<b>Outside Diameter:</b>	0.495 Inches Minimum And 0.520 Inches Maximum
<b>Retainer Thickness:</b>	0.045 Inches Minimum And 0.055 Inches Maximum
<b>Packing Ring Cross-sectional Diameter:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Packing Inside Diameter:</b>	0.230 Inches Minimum And 0.250 Inches Maximum
<b>Construction:</b>	One-piece
<b>Material:</b>	Rubber Fluorosilicone Class Fq Packing
<b>Material:</b>	Steel Comp 301 Retainer Or Steel Comp 302 Retainer
<b>Material Document And Classification:</b>	Mil-r-25988 Ty 1 Cl 1 Gr 70 Mil Spec Single Material Response Packing
<b>Material Document And Classification:</b>	Mil-s-5059 Cond Annealed Or Half Hard Mil Spec All Material Responses Retainer
<b>Surface Treatment:</b>	Passivate Retainer
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Retainer
<b>Specification/standard Data:</b>	80205-nas 1523 Professional/industrial Association Standard

## How to Order

Order this packing with retainer from our inventory online by visiting [https://military-fasteners.com/o\\_rings/packing+with+retainers/NAS1523C4R](https://military-fasteners.com/o_rings/packing+with+retainers/NAS1523C4R) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.