

Description

Fastener Length: 35/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1526H05
Minimum Qty (MOQ):	35 EA
NSN:	5320-00-467-0517
Schedule B:	7616.10.5000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N NAS1526H05 Specifications

<b>Fastener Length:</b>	0.536 Inches Minimum And 0.556 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.099 Inches Minimum And 0.111 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.297 Inches Minimum And 0.327 Inches Maximum
<b>Grip Length:</b>	0.282 Inches Minimum And 0.344 Inches Maximum
<b>Shear Strength:</b>	2520 Double Pounds Per Square Inch
<b>Heat Treatment:</b>	T-6 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1526 Professional/industrial Association Standard

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1526H05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.