

**Description**

Fastener Length: 4-1/2", Thread: 3/4-16, Head Width: 5/8", Thread Length: 1-5/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS152A72
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-041-9621
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS152A72 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.037 Inches Minimum And 1.087 Inches Maximum
<b>Fastener Length:</b>	4.485 Inches Minimum And 4.515 Inches Maximum
<b>Head Style:</b>	Bevel-conical
<b>Head Diameter:</b>	1.175 Inches Minimum And 1.188 Inches Maximum
<b>Head Height:</b>	0.732 Inches Nominal
<b>Shank Unthreaded Hole Diameter:</b>	0.141 Inches Minimum First Hole And 0.146 Inches Maximum First Hole
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.750 Inches
<b>Width Across Flats:</b>	0.626 Inches Minimum And 0.630 Inches Maximum
<b>Thread Quantity Per Inch:</b>	16
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	4.313 Inches Nominal First Hole
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 1335 Overall Or Steel Comp 1340 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas152 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS152A72> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.