



Military-Fasteners.com

P/N NAS152A72

Description

Fastener Length: 4-1/2", Thread: 3/4-16, Head Width: 5/8", Thread Length: 1-5/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS152A72
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-041-9621
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS152A72 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.037 Inches Minimum And 1.087 Inches Maximum
Fastener Length:	4.485 Inches Minimum And 4.515 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	1.175 Inches Minimum And 1.188 Inches Maximum
Head Height:	0.732 Inches Nominal
Shank Unthreaded Hole Diameter:	0.141 Inches Minimum First Hole And 0.146 Inches Maximum First Hole
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.750 Inches
Width Across Flats:	0.626 Inches Minimum And 0.630 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	4.313 Inches Nominal First Hole
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 1335 Overall Or Steel Comp 1340 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas152 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS152A72> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.