

Description

NAS1564-6-4 Tube Reducer Body

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS156464
Minimum Qty (MOQ):	10
NSN:	4730-00-759-3876
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N NAS1564-6-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Overall Length:	0.954 Inches Minimum And 0.984 Inches Maximum
Thread Size:	7/16-20
Tube Outside Diameter For Which Designed:	0.250 Inches Nominal
Tube Outside Diameter For Which Designed:	0.375 Inches Nominal
First End Seat Angle In Deg:	37.0
Second End Seat Angle In Deg:	37.0
Flange Width:	0.157 Inches Minimum And 0.187 Inches Maximum
Flange Outside Diameter:	0.499 Inches Minimum And 0.502 Inches Maximum
Screw Thread Series Designator:	Unf
Working Pressure And Service Type:	3000.0 Pounds Per Square Inch Nominal Any Acceptable
Working Temp And Service Type:	Not Rated
Material:	Steel, Qq-s-637, Comp 1137 Or Steel, Qq-s-637, Comp 1141 Or Steel, Mil-s-6758, Comp 4130 Or Steel, Mil-s-5626, Comp 4140
Material:	Steel Comp 1137 Or Steel Comp 1141 Or Steel Comp 4130 Or Steel Comp 4140
Surface Treatment:	Cadmium
Style Designator:	Reducer Body
Surface Treatment:	Cadmium, Qq-p-416, Type 1, Class 2
Specification/standard Data:	80205-nas1564 Professional/industrial Association Standard

How to Order

Order this tube reducer body from our inventory online by visiting <https://military-fasteners.com/fittings/tube+reducer+body/NAS1564-6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.