

**Description**

NAS1564 series reducer

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1564D84
Minimum Qty (MOQ):	5
NSN:	4730-00-053-0365
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



\* See page 2 for technical characteristics

## P/N NAS1564D8-4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Overall Length:</b>	1.015 Inches Minimum And 1.047 Inches Maximum
<b>Thread Size:</b>	7/16-20
<b>Tube Outside Diameter For Which Designed:</b>	0.250 Inches Nominal
<b>First End Seat Angle In Deg:</b>	37.0
<b>Second End Seat Angle In Deg:</b>	37.0
<b>Flange Width:</b>	0.203 Inches Minimum And 0.234 Inches Maximum
<b>Flange Outside Diameter:</b>	0.682 Inches Nominal
<b>Screw Thread Series Designator:</b>	Unf
<b>Working Pressure And Service Type:</b>	3000.0 Pounds Per Square Inch Nominal Any Acceptable
<b>Working Temp And Service Type:</b>	380.0 Deg Fahrenheit Nominal Any Acceptable
<b>Material:</b>	Aluminum Alloy, Qq-a-225/4, Alloy 2014, T6 Or Aluminum Alloy, Qq-a-225/6, Alloy 2024, T6 Or Aluminum Alloy, Qq-a-225/6, Alloy 2024, T851
<b>Material:</b>	Aluminum Alloy 2014 Or Aluminum Alloy 2024 Or Aluminum Alloy 2024
<b>Surface Treatment:</b>	Anodize
<b>Style Designator:</b>	Reducer Body
<b>Surface Treatment:</b>	Anodized, Mil-a-8625, Type 2, Class 2
<b>Specification/standard Data:</b>	80205-nas1564 Professional/Industrial Association Standard

## How to Order

Order this tube reducer body from our inventory online by visiting <https://military-fasteners.com/fittings/tube+reducer+body/NAS1564D8-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.