

Description

NAS1564 series reducer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1564D84
Minimum Qty (MOQ):	5
NSN:	4730-00-053-0365
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



P/N NAS1564D8-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Overall Length:	1.015 Inches Minimum And 1.047 Inches Maximum
Thread Size:	7/16-20
Tube Outside Diameter For Which Designed:	0.250 Inches Nominal
First End Seat Angle In Deg:	37.0
Second End Seat Angle In Deg:	37.0
Flange Width:	0.203 Inches Minimum And 0.234 Inches Maximum
Flange Outside Diameter:	0.682 Inches Nominal
Screw Thread Series Designator:	Unf
Working Pressure And Service Type:	3000.0 Pounds Per Square Inch Nominal Any Acceptable
Working Temp And Service Type:	380.0 Deg Fahrenheit Nominal Any Acceptable
Material:	Aluminum Alloy, Qq-a-225/4, Alloy 2014, T6 Or Aluminum Alloy, Qq-a-225/6, Alloy 2024, T6 Or Aluminum Alloy, Qq-a-225/6, Alloy 2024, T851
Material:	Aluminum Alloy 2014 Or Aluminum Alloy 2024 Or Aluminum Alloy 2024
Surface Treatment:	Anodize
Style Designator:	Reducer Body
Surface Treatment:	Anodized, Mil-a-8625, Type 2, Class 2
Specification/standard Data:	80205-nas1564 Professional/industrial Association Standard

How to Order

Order this tube reducer body from our inventory online by visiting <https://military-fasteners.com/fittings/tube+reducer+body/NAS1564D8-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.