

**Description**

Fastener Length: 1-15/16", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1578A3R25                              |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5305-01-365-4869                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1578A3R25 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.363 Inches Nominal  |
| <b>Fastener Length:</b>                               | 1.910 Inches Minimum And 1.940 Inches Maximum   |
| <b>Head Style:</b>                                    | Pan No. 2   |
| <b>Head Diameter:</b>                                 | 0.360 Inches Minimum And 0.375 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.115 Inches Minimum And 0.125 Inches Maximum   |
| <b>Grip Diameter:</b>                                 | 0.1890 Inches Minimum And 0.1895 Inches Maximum   |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 1.552 Inches Minimum And 1.572 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch   |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall Or Chromate Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec 1st Treatment Response Overall Or Qq-p-416,cl 2,ty 2 Fed Spec 2nd Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas1578 Professional/industrial Association Standard  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578A3R25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.