

## **P/N NAS1578A3R4L**

### **Description**

Fastener Length: 5/8", Thread: 10-32, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1578A3R4L

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-272-7436

Schedule B: 7616.10.9090

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1578A3R4L Specifications

| Thread Class:                                  | 3a   |
|--|--|
| Thread Direction:                              | Right-hand   |
| Thread Length:                                 | 0.338 Inches Minimum And 0.388 Inches Maximum  |
| Fastener Length:                               | 0.598 Inches Minimum And 0.628 Inches Maximum  |
| Head Style:                                    | Pan No. 2  |
| Head Diameter:                                 | 0.360 Inches Minimum And 0.374 Inches Maximum  |
| Head Height:                                   | 0.115 Inches Minimum And 0.125 Inches Maximum  |
| Locking Feature:                               | Patch Threads  |
| Grip Diameter:                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum  |
| Internal Drive Style:                          | Torque-set Ribbed  |
| Nominal Thread Diameter:                       | 0.190 Inches   |
| Grip Length:                                   | 0.240 Inches Minimum And 0.260 Inches Maximum  |
| Thread Quantity Per Inch:                      | 32   |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch  |
| Hardness Rating:                               | 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener  |
| Surface Finish:                                | 32.0 Microinches Bearing Surface Of Head   |
| Surface Finish:                                | 32.0 Microinches Grip  |
| Surface Finish:                                | 32.0 Microinches Threads   |
| Material:                                      | Plastic Locking Feature  |
| Material:                                      | Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener  |
| Material Document And Classification:          | Mil-s-5626 Mil Spec 1st Material Response Fastener Or Mil-s-5000 Mil Spec 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 3rd Material Response Fastener |
| Surface Treatment:                             | Cadmium Fastener And Chromate Fastener   |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Fastener  |
| Thread Series Designator:                      | Unjf   |
| Specification/standard Data:                   | 80205-nas1578 Professional/industrial Association Standard   |

## **How to Order**

