

Description

Fastener Length: 7/8", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1578A3R8 |
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5305-01-058-3931 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1578A3R8 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.338 Inches Minimum And 0.388 Inches Maximum |
| Fastener Length: | 0.848 Inches Minimum And 0.878 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.360 Inches Minimum And 0.374 Inches Maximum |
| Head Height: | 0.115 Inches Minimum And 0.125 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Special Features: | Internal Drive Ribbed |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-8503 Mil Spec 5th Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,c1 2 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas 1578 Professional/Industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578A3R8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.