

## Description

length: 0.801", thread: 10-32, flat pan head bolt - alloy steel offset cruciform"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1578A3T7                               |
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5305-01-058-8430                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1578A3T7 Specifications

|                                     |  |
|-------------------------------------|--|
| <b>Thread Class:</b>                | 3a   |
| <b>Thread Direction:</b>            | Right-hand   |
| <b>Thread Length:</b>               | 0.338 Inches Minimum And 0.388 Inches Maximum  |
| <b>Fastener Length:</b>             | 0.786 Inches Minimum And 0.816 Inches Maximum  |
| <b>Head Style:</b>                  | Pan No. 2  |
| <b>Head Diameter:</b>               | 0.360 Inches Minimum And 0.374 Inches Maximum  |
| <b>Head Height:</b>                 | 0.115 Inches Minimum And 0.125 Inches Maximum  |
| <b>Grip Diameter:</b>               | 0.1885 Inches Minimum And 0.1895 Inches Maximum  |
| <b>Internal Drive Style:</b>        | Offset Cruciform (torque Set)  |
| <b>Nominal Thread Diameter:</b>     | 0.190 Inches   |
| <b>Grip Length:</b>                 | 0.428 Inches Minimum And 0.448 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>    | 32   |
| <b>Minimum Tensile Strength:</b>    | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>             | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  |
| <b>Surface Finish:</b>              | 32.0 Microinches Bearing Surface Of Head   |
| <b>Surface Finish:</b>              | 32.0 Microinches Grip  |
| <b>Surface Finish:</b>              | 32.0 Microinches Threads   |
| <b>Material:</b>                    | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall |
| <b>Surface Treatment:</b>           | Cadmium Overall And Chromate Overall   |
| <b>Thread Series Designator:</b>    | Unjf   |
| <b>Specification/standard Data:</b> | 80205-nas1578 Professional/industrial Association Standard   |

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1578A3T7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.