

Description

length: 0.965", thread: 1/4-28, flat pan head bolt, alloy steel offset cruciform

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1578A4T9
Minimum Qty (MOQ):	25
NSN:	5305-01-058-7072
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1578A4T9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.378 Inches Minimum And 0.428 Inches Maximum
Fastener Length:	0.950 Inches Minimum And 0.980 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.477 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.140 Inches Minimum And 0.150 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1578 Professional/Industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1578A4T9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.