

Description

Fastener Length: 2-29/64", Thread: 1/4-24, Thread Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1578A5R31
Minimum Qty (MOQ):	1
NSN:	5305-01-501-6620
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS1578A5R31 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.501 Inches Nominal
Fastener Length:	2.424 Inches Minimum And 2.454 Inches Maximum
Head Style:	Pan
Head Diameter:	0.597 Inches Minimum And 0.612 Inches Maximum
Head Height:	0.176 Inches Minimum And 0.183 Inches Maximum
Grip Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.928 Inches Minimum And 1.948 Inches Maximum
Thread Quantity Per Inch:	24
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams6415 Assn Std 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578A5R31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.