

Description

Fastener Length: 2-29/64", Thread: 1/4-24, Thread Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1578A5R31 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5305-01-501-6620 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS1578A5R31 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.501 Inches Nominal |
| Fastener Length: | 2.424 Inches Minimum And 2.454 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.597 Inches Minimum And 0.612 Inches Maximum |
| Head Height: | 0.176 Inches Minimum And 0.183 Inches Maximum |
| Grip Diameter: | 0.311 Inches Minimum And 0.312 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.928 Inches Minimum And 1.948 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Material: | Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams6415 Assn Std 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578A5R31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.