

**Description**

Fastener Length: 2-29/64", Thread: 1/4-24, Thread Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1578A5R31
Minimum Qty (MOQ):	1
NSN:	5305-01-501-6620
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1578A5R31 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.501 Inches Nominal
<b>Fastener Length:</b>	2.424 Inches Minimum And 2.454 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.597 Inches Minimum And 0.612 Inches Maximum
<b>Head Height:</b>	0.176 Inches Minimum And 0.183 Inches Maximum
<b>Grip Diameter:</b>	0.311 Inches Minimum And 0.312 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	1.928 Inches Minimum And 1.948 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams6415 Assn Std 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578A5R31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.