

# P/N NAS1578A6T14

Military-Fasteners.com

#### Description

Fastener Length: 1-31/64", Thread: 3/8-24, Thread Length: 19/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS1578A6T14
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-374-5947
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1578A6T14 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Nominal
Fastener Length:	1.454 Inches Minimum And 1.484 Inches Maximum
Head Style:	Pan
Head Diameter:	0.722 Inches Minimum And 0.740 Inches Maximum
Head Height:	0.204 Inches Minimum And 0.220 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1578 Professional/industrial Association Standard

### How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578A6T14</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.