

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1578C3R1
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-372-5329
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1578C3R1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Nominal
Fastener Length:	0.410 Inches Minimum And 0.440 Inches Maximum
Head Style:	Pan
Head Diameter:	0.360 Inches Minimum And 0.374 Inches Maximum
Head Height:	0.115 Inches Minimum And 0.125 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1578 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578C3R1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.