

**Description**

Fastener Length: 1-7/8", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1578C3R24
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-515-8004
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N NAS1578C3R24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.363 Inches Minimum
<b>Fastener Length:</b>	1.848 Inches Minimum And 1.878 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.360 Inches Minimum And 0.374 Inches Maximum
<b>Head Height:</b>	0.115 Inches Minimum And 0.125 Inches Maximum
<b>Internal Drive Style:</b>	Torque Set
<b>End Item Identification:</b>	Naces
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Screw Material:</b>	Iron Alloy 660
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578C3R24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.