

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1578C3T12
Minimum Qty (MOQ):	10
NSN:	5305-01-592-8381
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS1578C3T12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Minimum And 0.388 Inches Maximum
Fastener Length:	1.098 Inches Minimum And 1.128 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.360 Inches Minimum And 0.374 Inches Maximum
Head Height:	0.115 Inches Minimum And 0.125 Inches Maximum
Grip Diameter:	0.188 Nominal Mils And 0.189 Nominal Centimeters
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.740 Nominal Mils And 0.760 Nominal Centimeters
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578C3T12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.