



Military-Fasteners.com

P/N NAS1578C3T3P

Description

length: 0.549", thread: 10-32, flat pan head bolt - cadmium plated corrosion resistant steel - offset cruciform

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1578C3T3P
Minimum Qty (MOQ):	5
NSN:	5306-01-468-4227
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1578C3T3P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.348 Inches Minimum And 0.378 Inches Maximum
Fastener Length:	0.348 Inches Minimum And 0.378 Inches Maximum
Head Style:	Undercut Pan No. 2
Head Diameter:	0.360 Inches Minimum And 0.374 Inches Maximum
Head Height:	0.115 Inches Minimum And 0.125 Inches Maximum
Nominal Thread Diameter:	0.1900 Inches
Thread Quantity Per Inch:	32
Thread Pitch In Millimeters:	2.3
External Thread Tolerance Class:	4h6h
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Overall And Ams5732 Assn Std 2nd Material Response Overall Or Ams5737 Assn Std 3rd Material Response Overall Or Ams5853 Assn Std 4th Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Overall Or Qq-p-416,typeii,class2 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578C3T3P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.