

## **P/N NAS1578C3T5**

### **Description**

length: 0.675", thread: 10-32, flat pan head bolt - corrosion resistant steel - offset cruciform

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1578C3T5

Minimum Qty (MOQ): 50

NSN: 5305-01-124-9017

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1578C3T5 Specifications

3a
Right-hand
0.338 Inches Minimum And 0.388 Inches Maximum
0.660 Inches Minimum And 0.690 Inches Maximum
Pan No. 2
0.360 Inches Minimum And 0.374 Inches Maximum
0.115 Inches Minimum And 0.125 Inches Maximum
0.1885 Inches Minimum And 0.1895 Inches Maximum
Offset Cruciform (torque Set)
0.190 Inches
0.302 Inches Minimum And 0.322 Inches Maximum
32
160000 Pounds Per Square Inch
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Iron Alloy 660 Overall
Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Passivate Overall
Qq-p-35 Fed Spec Single Treatment Response Overall
Unjf
80205-nas1578 Professional/industrial Association Standard

## **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578C3T5">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578C3T5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578C3T5">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578C3T5</a> and selecting the