

Description

Fastener Length: 7/8", Thread: 10-32, Thread Length: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1578C3T8 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-099-7213 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1578C3T8 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.338 Inches Minimum And 0.388 Inches Maximum |
| Fastener Length: | 0.848 Inches Minimum And 0.878 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.360 Inches Minimum And 0.374 Inches Maximum |
| Head Height: | 0.115 Inches Minimum And 0.125 Inches Maximum |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1578 Professional/Industrial Association Standard |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1578C3T8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.