

Description

Fastener Length: 23/32", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | NAS1578C4R5 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-202-2679 |
| Schedule B: | 7318.15.2091 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1578C4R5 Specifications

| | |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.378 Inches Minimum And 0.428 Inches Maximum |
| Fastener Length: | 0.700 Inches Minimum And 0.730 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.477 Inches Minimum And 0.492 Inches Maximum |
| Head Height: | 0.140 Inches Minimum And 0.150 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Special Features: | Internal Drive Ribbed |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1578 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578C4R5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.