



Military-Fasteners.com

P/N NAS1578C4T6

Description

Fastener Length: 25/32", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1578C4T6
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-217-4006
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1578C4T6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.378 Inches Minimum And 0.428 Inches Maximum
Fastener Length:	0.763 Inches Minimum And 0.793 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.472 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.140 Inches Minimum And 0.150 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5732 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1578 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578C4T6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.