

P/N NAS1578C4T8

Military-Fasteners.com

Description

Fastener Length: 29/32", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS1578C4T8
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-113-9793
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1578C4T8 Specifications

Thread Direction:Right-handThread Length:0.378 Inches Minimum And 0.428 Inches MaximumFastener Length:0.888 Inches Minimum And 0.918 Inches MaximumHead Style:Pan No. 2Head Biameter:0.477 Inches Minimum And 0.492 Inches MaximumHead Height:0.477 Inches Minimum And 0.492 Inches MaximumGrip Diameter:0.4471 Inches Minimum And 0.492 Inches MaximumGrip Diameter:0.4485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:0.550 Inches Minimum And 0.2495 Inches MaximumMomial Thread Diameter:0.250 Inches0.490 Inches Minimum And 0.510 Inches MaximumThread Quantity Per Inch:2828160000 Pounds Per Square InchMardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Per Stragteriat10.4006 OverallMaterial Document And Classification:Ris 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:pasivate OverallSurface Treatment And Classification:Single Single Treatment Response Overall		
Thread Length:0.378 Inches Minimum And 0.428 Inches MaximumFastener Length:0.888 Inches Minimum And 0.918 Inches MaximumHead Style:Pan No. 2Head Dlameter:0.477 Inches Minimum And 0.492 Inches MaximumBrade Height:0.140 Inches Minimum And 0.495 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumBrade Height:0.410 Inches Minimum And 0.2495 Inches MaximumBrade Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumBrade Diameter:0.550 InchesNominal Thread Diameter:0.520 InchesBrade Quantity Per Inch:0.490 Inches Minimum And 0.510 Inches MaximumBrade Quantity Per Inch:0.490 Inches Style:Brade Construction1.6000 Pounds Per Square InchBrade Stratig:0.400 Rouksell Construction Overall And 35.0 Rockwell CMaximum OverallBrades Rating:0.200 Microinches Strate Of HeadSurface Finish:3.20 Microinches ThreadsBurface Finish:3.20 Microinches GripSurface Finish:3.20 Microinches ThreadsMaterial Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:passitae OverallSurface Treatment:0.400 Soural Engense OverallBrade Diage Strate OverallSoural Engense OverallSurface Treatment:0.400 Soural Engense OverallBrade Diage Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:0.400 SouralBrade Diage Material Response Overall <th>Thread Class:</th> <td>За</td>	Thread Class:	За
Fastener Length:0.888 Inches Minimum And 0.918 Inches MaximumHead Style:Pan No. 2Head Diameter:0.477 Inches Minimum And 0.492 Inches MaximumHead Height:0.140 Inches Minimum And 0.150 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 Inches0.500 Inches Minimum And 0.510 Inches MaximumThread Quantity Per Inch:0.490 Inches Minimum And 0.510 Inches MaximumThread Quantity Per Inch:280.6000 Pounds Per Square InchHardness Rating:2.0000 Pounds Per Square InchSurface Finish:3.2.0 Microinches Bearing Surface Of HeadSurface Finish:3.2.0 Microinches GripSurface Finish:3.2.0 Microinches GripMaterial Document And Classification:ms 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single M	Thread Direction:	Right-hand
Head Style:Pan No. 2Head Diameter:0.477 Inches Minimum And 0.492 Inches MaximumHead Height:0.140 Inches Minimum And 0.150 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:Offset Cruciform (torque Set)Nomial Thread Diameter:0.250 InchesGrip Length:0.490 Inches Minimum And 0.510 Inches MaximumThread Quartity Per Inch:0.490 Inches Minimum And 0.510 Inches MaximumThread Quartity Per Inch:16000 Pounds Per Square InchHardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Baring Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial Document And Classificatio:Ross731 Assn Std Single Material Response Overall Or Ans 5732 Assn Std Single Material Response OverallSurface Treatment:Pasiyace OverallSurface Treatment Document And Classificatio:Q-p-35 Fed Spec Single Treatment Response Overall	Thread Length:	0.378 Inches Minimum And 0.428 Inches Maximum
Head Diameter:0.477 Inches Minimum And 0.492 Inches MaximumHead Height:0.140 Inches Minimum And 0.150 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:Offset Cruciform (torque Set)Nominal Thread Dlameter:0.250 InchesGrip Length:0.490 Inches Minimum And 0.510 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:85.0 Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:Passivate	Fastener Length:	0.888 Inches Minimum And 0.918 Inches Maximum
Head Height:0.140 Inches Minimum And 0.150 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:Offset Cruciform (torque Set)Nominal Thread Diameter:0.250 Inches0.490 Inches Minimum And 0.510 Inches MaximumOffset Cruciform (torque Set)Thread Quantity Per Inch:0.490 Inches Minimum And 0.510 Inches MaximumThread Quantity Per Inch:16000 Pounds Per Square InchHardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:Sinole Gol OverallMaterial Document And Classification:Mis S731 Assn Std Single Material Response Overall Or Ams S732 Assn Std Single Material Response OverallSurface Treatment:Pasivate OverallSurface Treatment Document AndOp-35 Fed Speel Single Treatment Response Overall	Head Style:	Pan No. 2
Grip Darweter:0.2485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:Offset Cruciform (torque Set)Nominal Thread Diameter:0.250 InchesGrip Length:0.490 Inches Minimum And 0.510 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Ross Stati Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:Pasivate OverallSurface Treatment Document AndQr.p-35 Fed Spec Single Treatment Response Overall	Head Diameter:	0.477 Inches Minimum And 0.492 Inches Maximum
Internal Drive Style:Offset Cruciform (torque Set)Nominal Thread Diameter:0.250 InchesGrip Length:0.490 Inches Minimu And 0.510 Inches MaximumThread Quantity Per Inch:8Minimu Tensile Strength:160000 Pounds Per Square InchHardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallSurface Finish:2.0 Microinches Bearing Surface Of HeadSurface Finish:2.0 Microinches GripSurface Finish:2.0 Microinches GripSurface Finish:2.0 Microinches GripSurface Finish:3.0 Microinches GripSurface Finish:3.0 Microinches Stating Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:Pasivate OverallSurface Treatment:Pasivate OverallSurface Treatment:Spes Schigle Treatment Response OverallSurface Treatment:Spes Schigle Treatment Response Overall	Head Height:	0.140 Inches Minimum And 0.150 Inches Maximum
Nominal Thread Diameter:0.250 InchesGrip Length:0.490 Inches Minimum And 0.510 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial:Iron Alloy 660 OverallSurface Treatment:Pasivate OverallPasivate OverallStrigt Agencial Response OverallSurface Treatment:Pasivate OverallSurface Treatment:OverallSurface Treatment:OverallSurface Treatment:OverallSurface Treatment:OverallSurface Treatment:OverallSurface Treatment:OverallSurface Treatment:OverallSurface Treatment:Pasivate OverallSurface Treatment:Surface Single Treatment Response OverallSurface Treatment:OverallSurface Treatment:Surface Single Single Treatment Response OverallSurface Treatment:Surface Single Sing	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Grip Length:0.490 Inches Minimum And 0.510 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:Pasivate OverallQuartice Treatment Document And Classification:Q-p-35 Fed Spec Single Treatment Response Overall	Internal Drive Style:	Offset Cruciform (torque Set)
Thread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:Pasivate OverallSurface Treatment Document And Classification:Q-p-35 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:Pasivate OverallQuep-35 Fed Spec Single Treatment Response Overall	Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Hardness Rating:24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:Pasivate OverallQuep-35 Fed Spec Single Treatment Response OverallQ-p-35 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	28
Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:ion Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment:Passivate OverallOutput Document And Classification:Output Document Response Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment:Passivate OverallQuep-35 Fed Spec Single Treatment Response Overall	Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Surface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qep-35 Fed Spec Single Treatment Response Overall	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response Overall	Surface Finish:	32.0 Microinches Grip
Material Document And Classification:Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response Overall	Surface Finish:	32.0 Microinches Threads
Material Document And Classification: Std Single Material Response Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Material:	Iron Alloy 660 Overall
Surface Treatment Document And Qq-p-35 Fed Spec Single Treatment Response Overall	Material Document And Classification:	
Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Surface Treatment:	Passivate Overall
Thread Series Designator: Unjf	Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578C4T8</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.