

**Description**

Fastener Length: 1-1/2", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS1578V3R18                         |
| Minimum Qty (MOQ):      | 115 EA                               |
| NSN:                    | 5305-01-330-9797                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | 9A991                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N NAS1578V3R18 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.363 Inches Nominal   |
| <b>Fastener Length:</b>                      | 1.473 Inches Minimum And 1.503 Inches Maximum  |
| <b>Head Style:</b>                           | Pan No. 2  |
| <b>Head Diameter:</b>                        | 0.360 Inches Minimum And 0.374 Inches Maximum  |
| <b>Head Height:</b>                          | 0.115 Inches Minimum And 0.125 Inches Maximum  |
| <b>Grip Diameter:</b>                        | 0.1890 Inches Minimum And 0.1895 Inches Maximum  |
| <b>Internal Drive Style:</b>                 | Torque-set Ribbed  |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches   |
| <b>Grip Length:</b>                          | 1.115 Inches Minimum And 1.135 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>             | 32   |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch  |
| <b>Material:</b>                             | Titanium Alloy Uns R56400 Overall  |
| <b>Material Document And Classification:</b> | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf   |
| <b>Specification/standard Data:</b>          | 80205-nas1578 Professional/Industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578V3R18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.