



Military-Fasteners.com

P/N NAS1578V3T30

Description

Fastener Length: 2-1/4", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1578V3T30
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-420-6725
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N NAS1578V3T30 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Maximum
Fastener Length:	2.223 Inches Minimum And 2.253 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.360 Inches Minimum And 0.374 Inches Maximum
Head Height:	0.115 Inches Minimum And 0.125 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.865 Inches Minimum And 1.885 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1578 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578V3T30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.