

**Description**

Fastener Length: 11/16", Thread: 10-32, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS1578V3T5                          |
| Minimum Qty (MOQ):      | 5                                    |
| NSN:                    | 5305-01-179-9470                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | EAR99                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N NAS1578V3T5 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.338 Inches Minimum And 0.388 Inches Maximum                 |
| <b>Fastener Length:</b>                      | 0.660 Inches Minimum And 0.690 Inches Maximum                 |
| <b>Head Style:</b>                           | Pan No. 2   |
| <b>Head Diameter:</b>                        | 0.360 Inches Minimum And 0.374 Inches Maximum                 |
| <b>Head Height:</b>                          | 0.115 Inches Minimum And 0.125 Inches Maximum                 |
| <b>Grip Diameter:</b>                        | 0.1890 Inches Minimum And 0.1895 Inches Maximum               |
| <b>Internal Drive Style:</b>                 | High-torque   |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches  |
| <b>Grip Length:</b>                          | 0.302 Inches Minimum And 0.322 Inches Maximum                 |
| <b>Thread Quantity Per Inch:</b>             | 32  |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                                 |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                                      |
| <b>Surface Finish:</b>                       | 32.0 Microinches Sides Of Head                                |
| <b>Material:</b>                             | Titanium Alloy Overall  |
| <b>Material Document And Classification:</b> | Ams4967,comp 6al-4v Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf  |
| <b>Specification/standard Data:</b>          | 80205-nas1578 Professional/industrial Association Standard    |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578V3T5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.