

**Description**

Fastener Length: 27/32", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS1578V4R7                          |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5305-01-220-9707                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | 9A991                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N NAS1578V4R7 Specifications

|                                              |                                                            |
|----------------------------------------------|------------------------------------------------------------|
| <b>Thread Class:</b>                         | 3a                                                         |
| <b>Thread Direction:</b>                     | Right-hand                                                 |
| <b>Thread Length:</b>                        | 0.378 Inches Minimum And 0.428 Inches Maximum              |
| <b>Fastener Length:</b>                      | 0.826 Inches Minimum And 0.856 Inches Maximum              |
| <b>Head Style:</b>                           | Pan No. 2                                                  |
| <b>Head Diameter:</b>                        | 0.477 Inches Minimum And 0.492 Inches Maximum              |
| <b>Head Height:</b>                          | 0.140 Inches Minimum And 0.150 Inches Maximum              |
| <b>Grip Diameter:</b>                        | 0.2490 Inches Minimum And 0.2495 Inches Maximum            |
| <b>Internal Drive Style:</b>                 | Offset Cruciform (torque Set)                              |
| <b>Nominal Thread Diameter:</b>              | 0.250 Inches                                               |
| <b>Grip Length:</b>                          | 0.428 Inches Minimum And 0.448 Inches Maximum              |
| <b>Thread Quantity Per Inch:</b>             | 28                                                         |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                              |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head                   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip                                      |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                                   |
| <b>Special Features:</b>                     | Internal Drive Ribbed                                      |
| <b>Material:</b>                             | Titanium Alloy Uns R56400 Overall                          |
| <b>Material Document And Classification:</b> | Ams 4967 Assn Std Single Material Response Overall         |
| <b>Thread Series Designator:</b>             | Unjf                                                       |
| <b>Specification/standard Data:</b>          | 80205-nas1578 Professional/industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578V4R7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.