

Description

Fastener Length: 21/32", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1578V4T4
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-326-5748
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS1578V4T4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.403 Inches Nominal
Fastener Length:	0.638 Inches Minimum And 0.668 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.477 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.140 Inches Minimum And 0.150 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1578 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578V4T4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.