

**Description**

Fastener Length: 0-63/64", Thread: 1/4-24, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1578V5T8L
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-590-9885
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



\* See page 2 for technical characteristics

# P/N NAS1578V5T8L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.501 Inches Nominal
Fastener Length:	0.986 Inches Minimum And 1.016 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.597 Inches Minimum And 0.612 Inches Maximum
Head Height:	0.176 Inches Minimum And 0.188 Inches Maximum
Locking Feature:	Patch Locking Feature
Grip Diameter:	0.311 Nominal Mils And 0.312 Nominal Centimeters
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.490 Nominal Mils And 0.510 Nominal Centimeters
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578V5T8L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.