

**Description**

Fastener Length: 0-63/64", Thread: 1/4-24, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1578V5T8L
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-590-9885
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N NAS1578V5T8L Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.501 Inches Nominal
<b>Fastener Length:</b>	0.986 Inches Minimum And 1.016 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.597 Inches Minimum And 0.612 Inches Maximum
<b>Head Height:</b>	0.176 Inches Minimum And 0.188 Inches Maximum
<b>Locking Feature:</b>	Patch Locking Feature
<b>Grip Diameter:</b>	0.311 Nominal Mils And 0.312 Nominal Centimeters
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	0.490 Nominal Mils And 0.510 Nominal Centimeters
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1578V5T8L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.