

P/N NAS1580A3R5

Description

Length: 11/16", Thread: 10-32, Thread Length: 3/8", NAS1580 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1580A3R5


Minimum Qty (MOQ): 25

NSN: 5305-01-163-8248

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1580A3R5 Specifications

3a
Right-hand
0.338 Inches Minimum And 0.388 Inches Maximum
0.660 Inches Minimum And 0.690 Inches Maximum
Flat Countersunk
0.339 Inches Minimum And 0.381 Inches Maximum
0.1885 Inches Minimum And 0.1895 Inches Maximum
Offset Cruciform (torque Set)
0.190 Inches
0.302 Inches Minimum And 0.322 Inches Maximum
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
99.0 Degrees Minimum And 101.0 Degrees Maximum
32.0 Microinches Grip
32.0 Microinches Threads
Internal Drive Ribbed
Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Cadmium Overall And Chromate Overall
Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas1580 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A3R5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A3R5 and selecting the