

Description

Fastener Length: 1-1/4", Thread: 10-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1580A3T14Y |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-01-169-6771 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1580A3T14Y Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.338 Inches Minimum And 0.388 Inches Maximum |
| Fastener Length: | 1.223 Inches Minimum And 1.253 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.339 Inches Minimum And 0.381 Inches Maximum |
| Shoulder Diameter: | 0.2197 Inches Minimum First Shoulder And 0.2207 Inches Maximum First Shoulder |
| Shoulder Length: | 0.865 Inches Minimum First Shoulder And 0.885 Inches Maximum First Shoulder |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Shoulder Shape: | Round First Shoulder |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1580 Professional/industrial Association Standard |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1580A3T14Y> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.