



★ FASTENERS

Military-Fasteners.com

P/N NAS1580A3T2

Description

length: 0.487", thread: 10-32, shear, flush head, alloy steel, offset cruciform, NAS1580 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580A3T2
Minimum Qty (MOQ):	50
NSN:	5305-01-061-0739
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1580A3T2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.337 Inches Minimum And 0.387 Inches Maximum
Fastener Length:	0.472 Inches Minimum And 0.502 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.339 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1580A3T2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.