

**Description**

Fastener Length: 1-13/16", Thread: 10-32, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS1580A3T23     |
| Minimum Qty (MOQ): | 50               |
| NSN:               | 5305-01-307-7898 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | EAR99            |



## P/N NAS1580A3T23 Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Thread Class:</b>                | 3a  |
| <b>Thread Direction:</b>            | Right-hand  |
| <b>Thread Length:</b>               | 0.338 Inches Minimum And 0.388 Inches Maximum                       |
| <b>Fastener Length:</b>             | 1.786 Inches Minimum And 1.816 Inches Maximum                       |
| <b>Head Style:</b>                  | Flat Countersunk  |
| <b>Head Diameter:</b>               | 0.339 Inches Minimum And 0.381 Inches Maximum                       |
| <b>Grip Diameter:</b>               | 0.188 Inches Minimum And 0.190 Inches Maximum                       |
| <b>Internal Drive Style:</b>        | Offset Cruciform (torque Set)                                       |
| <b>Nominal Thread Diameter:</b>     | 0.190 Inches  |
| <b>Grip Length:</b>                 | 1.428 Inches Minimum And 1.448 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>    | 32  |
| <b>Minimum Tensile Strength:</b>    | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>             | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Countersink Angle:</b>           | 99.0 Degrees Minimum And 101.0 Degrees Maximum                      |
| <b>Surface Finish:</b>              | 32.0 Microinches Bearing Surface Of Head                            |
| <b>Material:</b>                    | Steel Comp 8740 Overall   |
| <b>Surface Treatment:</b>           | Cadmium Overall Or Chromate Overall                                 |
| <b>Thread Series Designator:</b>    | Unjf  |
| <b>Specification/standard Data:</b> | 80205-nas1580 Professional/industrial Association Standard          |

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A3T23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.