

## P/N NAS1580A3T23

## **Description**

Fastener Length: 1-13/16", Thread: 10-32, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1580A3T23

Minimum Qty (MOQ): 50

NSN: 5305-01-307-7898

Schedule B: 7318.15.8085

ECCN: EAR99







<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1580A3T23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Minimum And 0.388 Inches Maximum
Fastener Length:	1.786 Inches Minimum And 1.816 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.339 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.190 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.428 Inches Minimum And 1.448 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:	Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall Or Chromate Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

### **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A3T23">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A3T23</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.