

Description

Fastener Length: 39/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1580A3T4DX
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-484-1292
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1580A3T4DX Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Nominal
Fastener Length:	0.598 Inches Minimum And 0.613 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.339 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.2041 Inches Minimum And 0.2051 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
End Item Identification:	F-16/b/c/d
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum
Material:	Iron Alloy 660 Overall
Surface Treatment Document And Classification:	Qq-o-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1580 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1580A3T4DX> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.